



# SUHNER® MICROWAVE CABLE DATA SHEET

## TYPE EZ 141-AL-TP/M17

*SEMI RIGID, the formstable microwave cable*

### Cable Design



	Material	Detail	Diameter
Centre conductor:	StCuAg	Wire	0.92 mm
Dielectric:	PTFE		2.98 mm
1. Outer conductor:	Al-TP Tube	100% coverage	3.58 mm

### Electrical Data

Impedance:	50	$\Omega$
Max. operating frequency:	20	GHz
Capacitance:	98.1	pF / m
Velocity of signal propagation:	69.5	%
Signal delay:	4.8	ns / m
Min. screening effectiveness:	> 120	dB (up to 18 GHz)
Max. operating voltage:	1.9	kV <sub>rms</sub> (at sea level)

### General Data

Temperature range:	-40 °C...+ 125 °C
Weight:	3.05 kg / 100 m
Min. bending radius :	static 3.18 mm

### Suitable Connectors

Cable group Y5 / Y12  
(for details refer to the "Suhner Microwave Cables and Assemblies General Catalogue" or contact you nearest HUBER+SUHNER partner)

### Notes

Order as **EZ 141-AL-TP/M17** under article number **22810015**

#### WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



**HUBER+SUHNER**

HUBER+SUHNER AG  
Interconnect Division  
CH-9100 Herisau  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
<http://www.hubersuhner.com>

Issued: 5.6.2002 10:30

Document: TEMP\_PDB\_2281001  
5.PDF

RF\_Co\_Ca\_PDF

uncontrolled copy

Page 1



# SUHNER® MICROWAVE CABLE DATA SHEET

## TYPE EZ 141-AL-TP/M17

**Matrix**      **Attenuation** [formula :  $(a \cdot f^{0.5} + b \cdot f)$ ] and **Power CW** [formula :  $(p / f^{0.5})$ ]

Coefficients:

a= 0.34536

b= 0.03967

f<sub>max</sub> = 20

p<sub>at 1GHz</sub> = 450

Frequency (GHz)	Nom. attenuation (dB / m) sea level 25° C ambient temperature	Nom. attenuation (dB / ft) sea level 25° C ambient temperature	Max. CW power (watt) sea level 40° C ambient temperature
0.5	0.26	0.079	636
1	0.39	0.119	450
2	0.57	0.174	318
3	0.72	0.219	260
4	0.85	0.259	225
5	0.97	0.296	201
6	1.08	0.329	184
7	1.19	0.363	170
8	1.29	0.393	159
9	1.39	0.424	150
10	1.49	0.454	142
11	1.58	0.482	136
12	1.67	0.509	130
13	1.76	0.536	125
14	1.85	0.564	120
15	1.93	0.588	116
16	2.02	0.616	113
17	2.10	0.640	109
18	2.18	0.664	106
19	2.26	0.689	103
20	2.34	0.713	101

### WAIVER!

While the information contained in this folder has been carefully compiled to the best of our present knowledge, it is not intended as representation or warranty of any kind on our part regarding the fitness of the products concerned for any particular use or purpose and neither shall any statement contained herein be constructed as a recommendation to infringe any industrial property rights or as a license to use any such rights. The fitness of each product for any particular purpose must be checked beforehand with our specialists.



**HUBER+SUHNER**

HUBER+SUHNER AG  
Interconnect Division  
CH-9100 Herisau  
Phone +41 (0)71 353 41 11  
Fax +41 (0)71 353 45 90  
<http://www.hubersuhner.com>

Issued: 5.6.2002 10:30

Document: TEMP\_PDB\_2281001  
5.PDF

RF\_Co\_Ca\_PDF

uncontrolled copy

Page 2