

# SUCOTEST® - stock assemblies

SUHNER assembly type	Order code	Length (mm)	Max. frequency (GHz)	Nom. IL (dB) *	Max. IL (dB) *	VSWR ≤
ST/ 2x N straight plug	23023671	500	13.0	0.88	0.95	1.25
ST/ N straight plug/SMA straight plug	23021755	500	13.0	0.88	0.95	1.25
ST/ 2x SMA straight plug	23021758	500	13.0	0.88	0.95	1.25
ST/ N straight plug/716 straight plug	23005051	1000	7.5	1.13	1.22	1.25
ST/ 2x N straight plug	23005046	1000	13.0	1.52	1.65	1.25
ST/ N straight plug/N-Quicklock straight plug	23005047	1000	13.0	1.52	1.65	1.25
ST/ N straight plug/N straight jack	23010003	1000	13.0	1.52	1.65	1.25
ST/ N straight plug/SMA straight plug	23005050	1000	13.0	1.52	1.65	1.25
ST/ N straight plug/TNC straight plug	23005048	1000	13.0	1.52	1.65	1.25
ST/ N straight plug/TNC-Quicklock straight plug	23005049	1000	13.0	1.52	1.65	1.25
ST/ 2x SMA straight plug	23021759	1000	13.0	1.52	1.65	1.25
ST/ 2x N straight plug	23023806	1500	13.0	2.17	2.36	1.25
ST/ N straight plug/SMA straight plug	23021756	1500	13.0	2.17	2.36	1.25
ST/ 2x SMA straight plug	23023255	1500	13.0	2.17	2.36	1.25
ST/ N straight plug/SMA straight plug	23021757	2000	13.0	2.81	3.06	1.25
ST/ 2x N straight plug	23019217	2000	13.0	2.81	3.06	1.25

\*@ 25 °C